

# DLCV OSCILLATOR



## Specifications


Parameters	Standard	Options
Frequency range	0,500 MHz - 200,000 MHz	
Logic output	HCMOS/TTL compatible	TTL only
Frequency stability		
Overall	+/- 50,0 ppm	+/-15,0 ppm best possible
Initial at 25°C	Please specify	
Temperature		
vs supply voltage change		
vs load change		
Aging first year		
Aging over .... Years		
Operating temperature	0° C ~ +70°C	-20°C ~ +70°C
		-40°C ~ +85°C
		Other on custom request
Storage temperature	-40°C ~ +85°C	-55°C ~ +125°C
Supply voltage	5,0 V ± 5% or 3,3 V ±5%	Other on custom request
Current	10 - 80 mA max	Other
Load	15 pF	Other - dependent of logic output
Rise/fall time	Other on custom request	
0,500 MHz - 7,999 MHz		
8,000 MHz - 79,999 MHz		
80,000 MHz -200,000 MHz		
Duty cycle	40/60 %	45/55 %
		Other on custom request
Phase noise	Please specify ( if required )	
Harmonics		
Sub-harmonics		
Jitter		
Start-up time	10 ms max.	Other on custom request
Frequency trimming range with externally adjustable trimmer		± 3 ppm min.
		Other

# DLCV OSCILLATOR

## Specifications

Parameters	Standard	Options
Linearity	± 10% max.	Other on custom request
Frequency tuning range	± 50 ppm - ± 200 ppm min	Other on custom request
Pulling slope	Positive	Other on custom request
External control voltage	+ 1,65 VDC ±1,65 VDC (3,3V) +2,5 VDC ±2,5 VDC (5,0V)	Other
Marking	Freq + Code + Week +Year	
Package	DIL14 DIL14-7 DIL14-9	

## Drawing



Case	H
DIL14	5.08
DIL14-7	7.48
DIL14-9	9.0

Pin configuration	#1: Control voltage	other pin configuration possible
	#7 : GND	
	#8 : Output	
	#14 : Vcc	