

# DLE OSCILLATOR



## Specifications


Parameters	Standard	Options
Frequency range	19,440 MHz - 700,0 MHz	
Logic output	LVPECL	PECL ECL
Frequency stability		
Overall	+/- 50 ppm	+/-15 ppm best possible
Initial at 25°C	Please specify	
Temperature		
vs supply voltage change		
vs load change		
Aging first year		
Aging over .... Years		
Operating temperature	0° C ~ +70°C	-20°C ~ +70°C -40°C ~ +85°C Other on custom request
Storage temperature	-40°C ~ +85°C	-55°C ~ +125°C
Supply voltage	3,3 V +/-5%	5,0 V +/-5% (-5,2 V for ECL ) Other on custom request
Current	80 mA max	
Load	Vcc-2,0 V into 50 ohm	
Rise/fall time	2 ns max	Other on custom request
Duty cycle	40/60 %	45/55 % Other on custom request
Jitter ( 12kHz ~20,0 MHz )	< 184,320 MHz : 1ps RMS > 184,320 MHz : 4,5 ps RMS	Other on custom request
Phase noise	Please specify ( if required )	
Harmonics		
Sub-harmonics		

# DLE OSCILLATOR

## Specifications

Parameters	Standard	Options
Start-up time	10 ms max.	Other on custom request
Tristate	Low or open = enable High = disable	no tristate
Marking	Freq + Code + Week +Year	
Package	DIL14 5 pin	DIL14 4pin

## Drawing



Pin configuration	#1: E/D or NC	other pin configuration possible
	#7 : GND	
	#8 : Output	
	#9 : Complimentary output	
	#14 : Vcc	